



# **Specification Sheet**

## **PolyPro 4000D 3.8 mil Receipt**

### **Features:**

- Direct thermal, matte polypropylene 3.8 mil receipt
- Excellent print quality
- Good scratch/smear resistance
- Not to be used in applications using chemicals
- Available in white (66554RM)

### **Suggested Applications:**

- General purpose ticketing
- Mobile point of sale receipts
- Work in process tagging
- Direct store delivery
- Receipt applications that may be exposed to moisture
- Archival use

### **Material Construction:**

	<b>Description</b>	<b>Caliper</b>
<b>Facestock</b>	White smooth topcoated direct thermal paper	3.8 mil
	<b>Total</b>	3.8 mil

### **Temperature Performance:**

- Minimum Application Temperature: NA
- Service Temperature: -40° F to 140° F (-40° C to 60° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Not recommended for outdoor use





# **Specification Sheet**

## **PolyPro 4000D 3.8 mil Receipt**

### **Chemical Resistance**

	<b>Weak</b>					<b>Moderate</b>				<b>Harsh</b>			<b>Extreme</b>				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
<b>DT</b>			X	X	X												

NOTE: For guidance only, not to be used for setting specifications

### **Product Performance and Suitability**

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

