



Specification Sheet

Z-Perform 1000D

Features:

- Direct thermal, smooth, paper label with a permanent acrylic adhesive
- Good print quality
- Limited resistance to moisture or abrasion
- Not recommended for high speed printing applications
- Topcoating is suitable for fanfolding
- Available in white (65832RM)

Suggested Applications:

- Indoor, general-purpose labeling
- Box labeling
- Compliance labeling
- Work-in-process labeling
- Food labeling

Material Construction:

	Description	Caliper
Facestock	White smooth topcoated paper	3.1 mil
Adhesive	Permanent, acrylic-based	0.7 mil
Liner	40 lb. semi-bleached, kraft stock	2.4 mil
Total		6.2 mil

Temperature Performance:

- Minimum Application Temperature: 25° F (-4° C)
- Service Temperature: -40° F to 140° F (-40° C to 60° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Not recommended for outdoor use





Specification Sheet

Z-Perform 1000D

Applications with Chemicals:

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
DT																	

NOTE: For guidance only, not to be used for setting specifications

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

