



Specification Sheet

Z-Perform 1000D 2.4 mil Receipt

Features:

- Direct thermal, smooth, uncoated 2.4 mil receipt paper
- Excellent print quality
- Available in white (05610RM)

Suggested Applications:

- General purpose ticketing
- Mobile point of sale receipts
- Work in process tagging
- Archival use

Material Construction:

	Description	Caliper
Facestock	White smooth uncoated direct thermal paper	2.4 mil
Total		2.4

Temperature Performance:

- Minimum Application Temperature: NA
- Service Temperature: -40° F to 140° F (-40° C to 60° C)
- Storage Conditions: 32° F to 70° F (0° C to 21° C) at 35% to 50% RH
- Expected Exterior Life: Not recommended for outdoor use





Specification Sheet

Z-Perform 1000D 2.4 mil Receipt

Chemical Resistance

	Weak					Moderate				Harsh			Extreme				
	Blood	Body Fluid	Salt Water	Water	Window Cleaner	Alcohol	Ammonia	Bleach	IPA	Gasoline	Grease	Oil	Acetone	IR Reflow	MEK	TCE	Xylene
DT																	

NOTE: For guidance only, not to be used for setting specifications

Product Performance and Suitability

The information contained in this document is to be used for guidance only and is not intended for use in setting specifications. All purchasers of Zebra products shall be solely responsible for independently determining if the product conforms to all requirements of their unique application.

